

**King Fahd University of
Petroleum & Minerals
Computer Engineering Dept**

**COE 341 – Data and Computer
Communications**

Term 082

Dr. Ashraf S. Hasan Mahmoud

Rm 22-148-3

Ext. 1724

Email: ashraf@kfupm.edu.sa

2/28/2009

Dr. Ashraf S. Hasan Mahmoud

1

Lecture Contents

1. Communication Model:
 - a. Main blocks and functionality
 - b. Communication Tasks
2. Data Communications
3. Data Communication Networking:
 - a. Wide area networks
 - i. Circuit switching
 - ii. Message switching
 - iii. Packet switching
 - iv. ATM
 - b. Local area networks

2/28/2009

Dr. Ashraf S. Hasan Mahmoud

2

Lecture Contents- cont'd


4. Protocols and Protocol Architecture (very brief – detailed in next set of slides)
 - a. Key elements of protocol
5. Protocol Standardization and Standards Organizations

2/28/2009

Dr. Ashraf S. Hasan Mahmoud

3

General Communications Model – Blocks and Functionality



- **Source:** Generates signal or data to be communicated
- **Transmitter:** Transforms and/or encodes information to be communicated
 - E.g. modulation – data encoding
- **Transmission System/Medium:** Transmission line, space, interconnected switching nodes, etc
- **Receiver:** accepts message and undoes transmitter procedures
 - E.g. demodulation – data decoding
- **Destination:** receives raw signal or data


2/28/2009

Dr. Ashraf S. Hasan Mahmoud

4


Communications Modes (Duplexity)

- **Modes:**
 - **Simplex:** one way – e.g. TV/Radio signals
 - **Half Duplex:** one direction at a time – walky talky and CB
 - **Full Duplex:** both directions – e.g. telephone
- **Due to device and/or communication medium limitations**




Simplex:
- only *one* path exists

2/28/2009



Half duplex:
- two paths exist
- one direction active at one time


Dr. Ashraf S. Hasan Mahmoud



Full duplex:
- two paths exist
- two directions may be active at one time

5

Communications Model – Example 1 - Analog (Simplex)



Source:
-Scene/audio to be transmitted

Transmission System/Medium:
- Overall signal broadcast
- Maybe relayed through intermediate satellite/ground station

Destination:
-Scene/audio

Transmitter:
- Converts info to electrical signals
- Electrical signals modulate carrier
- Amplification and transmission using antennas


Receiver:
- Receives electromagnetic signal
- Demodulates received signal and extracts original electrical signal
- generates original scene/audio information

2/28/2009

Dr. Ashraf S. Hasan Mahmoud

6

Communications Model – Example 2 (Full Duplex)



Source:

- User data to be *exchanged*

Transmitter (Modem):

- Encodes data
- Encoded data modulates carrier
- Amplification and transmission using phone line

Transmission System/Medium:

- Public switched telephony network

Receiver:

- Receives electrical signal
- Demodulates received signal and extracts original encoded data
- data is decoded to obtain original data

Destination:

- User data

2/28/2009

Dr. Ashraf S. Hasan Mahmoud

7

Communications Tasks


Task Name	Comments
Transmission System Utilization	Maximize usage of medium capacity through multiplexing, efficient/advanced comm techniques, etc.
Interfacing	The transport of signal from device to medium
Signal Generation	Creation of signal that is matched to the transmission medium and has original data
Synchronization	Orchestrated and coordinated operation of both transmitter and receiver
Error Detection and Correction	When errors can not be tolerated, a mechanism is required to detect and may be correct errors
Recovery	Reset of communication path
Addressing and Routing	For shared media – need to redirect comm using destination address
Network Management	Configuration – monitoring – signaling (typically not part of user comm)
Message formatting	The form of messages to be transmitted
Exchange Management	Coordination and cooperation of two communicating ends during session
Security	Encryption/Decryption of messages

2/28/2009

Dr. Ashraf S. Hasan Mahmoud

8

Data Communications



- **Characteristics:**

- May involve buffering and/or encoding of digital data (chapter 5)
- Modulated signal $s(t)$ matched to media (chapter 3/4)
- Transmission impairments: noise, distortion, etc (section 3.3)
- Ideally received info m' should be identical to original input info m (chapter 7)
- If not, error correction may help restore m (chapter 7)
- Else, retransmission is required (chapter 7)

2/28/2009



Dr. Ashraf S. Hasan Mahmoud

9

Data Communication Networking

- **Full Connectivity of N nodes:**

- Using dedicated links from each node to every other nodes – number of links is $N*(N-1)/2 = O(N^2)$
 - Expensive
 - Difficult manage and scale
 - Not reliable – one path *only* between any two nodes
- Use a **communication network** to interconnect nodes
 - No dedicated links or connections for every path
 - reduced number of links
 - easier to manage – flexibility and scalability



2/28/2009

Dr. Ashraf S. Hasan Mahmoud

10

Logical Topology Classification and Requirements

- **Logical Topology for Networks:**
 - Point-to-Point,
 - Multi-access links,
 - Internetworks
- **Logical topology point of view**
- **May differ from physical implementation**


2/28/2009

Dr. Ashraf S. Hasan Mahmoud

11

Logical Topology Classification and Requirements – cont'd

- **Point-to-Point:**
 - *No addressing is required*
 - **Medium: cables, air (wireless), fiber, etc.**




2/28/2009

Dr. Ashraf S. Hasan Mahmoud

12

Logical Topology Classification and Requirements – cont'd

- **Multi-access links:**
 - *Addressing is REQUIRED*
 - **Medium:** cables, air (wireless), fiber, etc.
 - **Media Access Control** – is a main function
 - Bus arbitration and access coordination to resolve contention




2/28/2009

Dr. Ashraf S. Hasan Mahmoud

13

Logical Topology Classification and Requirements – cont'd

- **Internetworks:**
 - *Addressing is REQUIRED*
 - *Routing is a main function:*
 - Selection of optimal path
 - Protocol translation may be required



2/28/2009

Dr. Ashraf S. Hasan Mahmoud

14

Logical Topology Classification and Requirements – cont'd

- **Local Area Network (LAN):**
 - Collection of nodes connected using point-to-point, or multi-access links
 - Example: Ethernet, token bus, FDDI, etc
- **Wide Area Network (WAN):**
 - Collection of LANs connected using protocol translators or gateways
 - Internetwork
- **Metropolitan Area Networks (MAN)**
- **Wireless Networks**

2/28/2009

Dr. Ashraf S. Hasan Mahmoud

15

Data Communication Networks

- **WANs (in more details):**
 - Span a large geographical area
 - Consists of a number of interconnected switching nodes
 - **Boundary v.s. Intermediate nodes:**
 - **Boundary:**
 - May perform control, management, translation functions
 - Pass (switch) user traffic to destination
 - **Intermediate:**
 - Pass (switch) traffic to destination

2/28/2009

Dr. Ashraf S. Hasan Mahmoud

16

Data Communication Networks – cont'd

- **Switching Technologies for WANs:**
 - **Circuit Switching**
 - **Packet Switching**
 - **Frame Relay**
 - **ATM**

2/28/2009

Dr. Ashraf S. Hasan Mahmoud

17

Data Communication Networks – cont'd

- **Circuit Switching**
 - **A dedicated “physical” communication path is established between the two ends**
 - **Path may be made of series of physical links**
 - **Intermediate nodes switch data or traffic from known input to known output ports with no delay**
 - **A communication session is usually divided into:**
 - **Call setup: dialup**
 - **Traffic exchange: conversation**
 - **Call termination: hang up**
 - **Example: public switching telephony network (PSTN)**

2/28/2009

Dr. Ashraf S. Hasan Mahmoud

18

Data Communication Networks – cont'd

- **Packet Switching**
 - Communicated data is divided into a sequence of chunks or “packets”
 - Each packet is passed from node to the next in the network along some path leading to the destination
 - At each node, the entire packet is received, stored briefly, and then forwarded to the next node
 - To combat errors:
 - Packets have overhead to correct/detect errors
 - Intermediate switching nodes may perform retransmission functions
 - Designed for link speed around 64 kbps
- **Example: The Internet**

2/28/2009

Dr. Ashraf S. Hasan Mahmoud

19

Data Communication Networks – cont'd

- **Frame Relay**
 - Newer technology compared to packet switching
 - Assumes more reliable transmission links and higher speeds – hence:
 - Overhead is not required
 - End nodes can detect and correct errors
 - Variable frame length
 - Up to 2 Mbps

2/28/2009

Dr. Ashraf S. Hasan Mahmoud

20

Data Communication Networks – cont'd


- **Asynchronous Transfer Mode (ATM)**
 - Cell relay technology
 - Assumes even more reliable transmission links and higher speeds than frame relay
 - Negligible overhead and no error protection for payloads
 - Fixed payload sizes (48 Bytes)
 - Switching hardware – extremely fast
 - Speeds up to Giga bps
 - Because of its high speed and efficiency, it can provide constant data rate connections (circuit switching) between two nodes

2/28/2009

Dr. Ashraf S. Hasan Mahmoud

21

Networking Configuration - Example



2/28/2009

Dr. A: