

COE 308 – Computer Architecture

Assignment 3: Floating-Point Representation and Arithmetic

Due Saturday, March 29, 2008

1. (4 pts) What is the decimal value of the following single-precision floating-point numbers?
 - a) 1010 1101 0001 0100 0000 0000 0000 0000 (binary)
 - b) 0100 0110 1100 1000 0000 0000 0000 0000 (binary)

2. (3 pts) Show the IEEE 754 binary representation for: -75.4 in ...
 - a) Single Precision
 - b) Double precision

3. (6 pts) $x = 1100\ 0110\ 1101\ 1000\ 0000\ 0000\ 0000\ 0000$ (binary)
and $y = 0011\ 1110\ 1110\ 0000\ 0000\ 0000\ 0000\ 0000$ (binary)
are single-precision floating-point numbers. Perform the following operations showing all work:
 - a) $x + y$
 - b) $x * y$

4. (4 pts) $x = 0101\ 1111\ 1011\ 1110\ 0100\ 0000\ 0000\ 0000$ (in binary)
and $y = 0011\ 1111\ 1111\ 1000\ 0000\ 0000\ 0000\ 0000$ (in binary)
and $z = 1101\ 1111\ 1011\ 1110\ 0100\ 0000\ 0000\ 0000$ (in binary)
represent single precision IEEE 754 floating-point numbers. Perform the following operations showing all work:
 - a) $x + y$
 - b) Result of (a) + z
 - c) Why is the result of (b) counterintuitive?

5. (3 pts) IA-32 offers an 80-bit extended precision option with a 1 bit sign, 16-bit exponent, and 63-bit fraction (64-bit significand including the implied 1 before the binary point). Assume that extended precision is similar to single and double precision.
 - a) What is the bias in the exponent?
 - b) What is the range (in absolute value) of normalized numbers that can be represented by the extended precision option?