Appendix B - Connector Reference Chart

Description	Male	Female	Side View	Common Applications
Amphenol 50 Pin	1 50	50		Telco, SCSI
Half Pitch Centronics 50 pin	1 [[1 50		SCSI
Half Pitch Centronics 68 pin	1 [[(1 [68		SCSI
BNC				LAN, Video
DIN 5 Pin	3 (1 2 5 3		AT Keyboard, Audio, MIDI
Mini-DIN 4 Pin	3 1	(1) 3 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1		Apple Destop Bus, SVHS, S-Video
Mini-DIN 6 Pin	5 3 1	5 1		PS/2 Keyboard/Mouse
RJ10	4 1 (1)			Telephone

EE 400 - Communications Networks Lab

RJ11	6 1			Telephone
RJ45	8 1 			ISDN, LAN
Sub-D 9 Pin	1 9	9 1		RS232, RS449, EGA, CGA
Sub-D 15 Pin	1 (*********) 15	1 15		X.21, Mac Video
Sub-D 25 Pin	1 ••••••••••••••••••••••••••••••••••••	25		RS232, Centronics
Sub-D 37 Pin	1 (************************************	37		RS449
Sub-D 50 Pin	1 17 33 50	17 1 33 50		SCSI
Sub-D 15 Pin High-Density	1 25 10 15	5 1 10 ***** 15		VGA, SVGA, XGA
13C3	A3 A2 1 A1 (O O O) 10	A1 1 A2 A3 •••••••• 10		Sun Work Station
ST	(b)	•	~= - [B)-	FDDI
MIC	•			FDDI

Copyright © Electrical Engineering Department, KFUPM.