


Features

- Vitreous china
- Elongated bowl
- Comfort Height®
- Includes seat and cover
- Less supply
- One-piece
- Power Lite® operating system (see electrical service requirements)
- 12" (305 mm) rough-in
- ADA compliant when installed following installation notes
- Includes Twin Touch™ actuator to select either 1.0 gal (3.8 L) flush or 1.4 (5.3 L) flush
- 12" (305 mm) x 10" (254 mm) water area
- 30" (762 mm) x 19-1/2" (495 mm) x 21-1/2" (546 mm)

COMFORT HEIGHT™ POWER LITE® TOILET K-3393



Codes/Standards Applicable

Specified model meets or exceeds the following:

- ADA
- ASME A112.19.2/CSA B45.1
- ICC/ANSI A117.1
- EPA WaterSense®
- UL 1951

Colors/Finishes

- 0: White
- Other: Refer to Price Book for additional colors/finishes

Accessories

- 0: White
- PB: Vibrant® Polished Brass
- Other: Refer to Price Book for additional colors/finishes

Specified Model

Model	Description	Colors/Finishes	
K-3393	Elongated bowl toilet	<input type="checkbox"/> 0	<input type="checkbox"/> Other_____
Optional Accessories			
K-4650	Lustra™ elongated open-front toilet seat - for ADA compliance	<input type="checkbox"/> 0	<input type="checkbox"/> Other_____
K-9433	Twin Touch™ actuator (non-CP)	<input type="checkbox"/> PB	<input type="checkbox"/> Other_____
1098663	Brass riser kit (when local codes require a rigid water supply)		

Product Specification

The one-piece Comfort Height toilet with elongated bowl shall be made of vitreous china. Toilet shall be 30" (762 mm) in length, 19-1/2" (495 mm) in width, and 21-1/2" (546 mm) in height with a 12" (305 mm) x 10" (254 mm) water area. Toilet shall feature the Power Lite® operating system and Twin Touch™ actuator to select either 1.0 gal (3.8 L) flush or 1.4 gal (5.3 L) flush. Toilet shall be 12" (305 mm) rough-in, and less supply. Toilet shall be ADA compliant (when installed following installation notes). Toilet shall include seat and cover. Toilet shall be Kohler Model K-3393-_____.

SAN RAPHAEL™

Technical Information

Fixture:	
Configuration	One-piece, elongated
Water per flush	1 gal (3.8 L) or 1.4 gal (5.3 L)
Passageway	2-1/8" (54 mm)
Water depth from rim	5-7/8" (149 mm)
Water area	12" (305 mm) x 10" (254 mm)
Seat post hole centers	5-1/2" (140 mm)
Pump	2 Hp, 120 V, 8.5 A, 60 Hz
Minimum static pressure required	15 psi (103.4 kPa)

Included components:	
Tank cover	1055954
Bolt cap accessory pack	1013092
Toilet seat	K-4713
Twin Touch™ dual flush selector	81996

Included components:

Tank accessory pack	84301
Pump	84153

Required Electrical Service

Dedicated circuit required, protected with Class A Ground-Fault Circuit-Interrupter (GFCI):

Receptacle	120 V, 15 A, 60 Hz
------------	--------------------


Installation Notes

Install this product according to the installation guide.

For back-to-back toilet installations: Use only a 45° double wye fitting.

Will comply with the American Disabilities Act (ADA) when installed per the requirements of the Accessibility Guidelines, Section 604 Water Closets, of the Act. The Model Plumbing Codes require the installation of elongated open-front toilet seats in public bathrooms.

Section 604 states the required height of the toilet is 17" (432 mm) to 19" (483 mm) from the floor to the top of the seat to meet ADA requirements.



Product Diagram